

GLOBAL FLANGED COMPOSITE HOSE



Application: Versatile, durable hose designed for the Pump Rental Industry, the Global Flanged Composite Hose replaces the heavy rubber suction and discharge hoses, commonly used in the pump rental market. This hose provides extreme flexibility, light-weight handling and excellent service life. Excellent for the transfer of water, dirty oily water and light chemicals.

Advantage:

- Crimped couplings
- Absorbs pump pulsations
- Less manpower to install than rubber hose
- Easy to package for shipping and storage
- Standard lengths: 10 ft & 20 ft

Temperature: up to 180°F
Fixed X Floating: CS 150 lb RF

PART NUMBER	DESCRIPTION	PSI RATING
601984000000	4" X 10' GLOBAL FLANGED COMPOSITE HOSE	250
601988000000	6" X 10' GLOBAL FLANGED COMPOSITE HOSE	250
601992000000	8" X 10' GLOBAL FLANGED COMPOSITE HOSE	250
601996000000	10" X 10' GLOBAL FLANGED COMPOSITE HOSE	250
602000000000	12" X 10' GLOBAL FLANGED COMPOSITE HOSE	250
601986000000	4" X 20' GLOBAL FLANGED COMPOSITE HOSE	250
601990000000	6" X 20' GLOBAL FLANGED COMPOSITE HOSE	250
601994000000	8" X 20' GLOBAL FLANGED COMPOSITE HOSE	250
601998000000	10" X 20' GLOBAL FLANGED COMPOSITE HOSE	250
602002000000	12" X 20' GLOBAL FLANGED COMPOSITE HOSE	250