

GLOBAL PUMP FUELCUBE



The transportable GLOBAL PUMP FUEL CUBE is a double-walled above ground fuel storage tank. It is specifically designed to provide on-demand fuel supply (environmentally and efficiently) for construction equipment and temporary power applications.

By transporting fuel to site with a GLOBAL PUMP FUELCUBE, you are ready to start up on arrival, without having to coordinate and wait for a fuel truck delivery. Once in place, the GLOBAL PUMP FUEL CUBE can be “quick-connected” directly to the engines of up to 3 pieces of diesel-powered equipment. Fuel can also be dispensed by manual or electric pump.

Extend your equipment run times, reduce your costs, and decrease the carbon footprint of your operations with the GLOBAL PUMP FUEL CUBE line of transportable fuel storage tanks!

FEATURES

Transportable.
Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.

Accessible.
Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.

Environmentally Safe.
Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved, designed to DOT standards.

Stackable.
Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.

Efficient.
ENVIROconnect Equipment Cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel powered equipment.

MODELS AND SPECIFICATIONS	GP-10TCG	GP-20TCG	GP-30TCG	GP-40TCG
Length	45.31" (1,151 mm)	90.31" (2,294 mm)	90.39" (2,296 mm)	90.87" (2,308 mm)
Width	45.31" (1,151 mm)	45.35" (1,152 mm)	60.87" (1,546 mm)	90.87" (2,308 mm)
Height	52.17" (1,325 mm)	52.13" (1,324 mm)	52.09" (1,323 mm)	44.84" (1,139 mm)
Empty	1,131 lbs (513 kg)	1,830 lbs (830 kg)	2,251 lbs (1,021 kg)	3,417 lbs (1,550 kg)
Full	3,199 lbs (1,451 kg)	6,508 lbs (2,952 kg)	8,766 lbs (3,976 kg)	12,024 lbs (5,454 kg)
Fuel Cell	251 Gal. (949 L)	552 Gal. (2,091 L)	787 Gal. (2,980 L)	1,056 Gal. (4,000 L)