GLOBAL PUMP A MERSINO COMPANY



SERVICE AND PRODUCTS design | manufacture | service | sell | rent





Standard Series

Standard Trash (GST)

Max flows from 1,250 to 16,000 gpm (284 to 3,634 m³/h) Max head from 116 to 202 ft (35 to 62 m)

High Head Trash (GHT)

Max flows from 1,600 to 16,000 gpm (341 to 3,634 m³/h) Max head from 169 to 261 ft (41 to 80 m)

High Head Series

Standard High Head (GSH)

Max flows from 1,380 to 6,750 gpm (313 to 1,533 m³/h) Max head from 340 to 433 ft (104 to 132 m)

High Performance High Head (GHH)

Max flows from 1,440 to 7,950 gpm (327 to 1,806 m³/h) Max head from 648 to 748 ft (198 to 228 m)

Global Pump Wellpoint Pumps

Centrifugal Wellpoint (GSCWP)

Max flows from 600 to 1,800 gpm (136 to 409 m³/h) Max head from 102 to 108 ft (31 to 33 m)

Rotary Wellpoint (GSRWP)

Max flows from 800 to 3,200 gpm (151 to 603 m 3 /h) Max head to 50 ft (15 m)

Piston Wellpoint (GSPWP)

Max flows from 360 gpm (82 m $^{3}/h$) Max head to 81 ft (27 m)

Global Pump Submersible Pumps

Trash/Water Models

1/2 hp to 60 hp (0.37 kW to 44.8 kW) 1" to 16" (25 to 406 mm)

Hard Iron Mine Dewatering and Dredging Models with Agitator Capacities to 5,300 gpm to 275 ft (1,203 m³/h at 84 m)

Accessories

Global SafeGuard and SoundGuard Enclosures

Generators

Road Ramps

20kW (25kVA) to 409kW (511kVA)

6" - 24" Global Pump Road Ramps

Hose

2" - 12" suction and discharge

Pipe

2" - 12" Global Pump QD galvanized pipe & fittings 6" - 36" HDPE Pipe and other pipe, hose & fittings

T-Floats

Light Towers

Fuel Cubes

Pneumatic Pipe Plugs

Spill Containment Berms

Small Gasoline Engine Portable Pumps and Generators

WWW.GLOBALPUMP.COM | 24 HOUR SERVICE | 1.866.360.PUMP

