

GLOBAL ORANGE SPIRAL SUCTION HOSE



Application: Water suction and discharge hose for heavy duty applications requiring combined vacuum and higher working pressures. Perfect for rental/construction pumping..

Tube: Flexible PVC, smooth bore)

Reinforcement: Rigid PVC helix

Cover: Synthetic braiding, corrugated O.D.

Temperature: -13°F to 140°F

Fittings: Global QD, Camlock, NPT

ID INCHES	OD INCHES	BEND RADIUS AT 72°F inches	WEIGHT lbs./ft
3	3.70	6	1.13
4	4.78	7	1.74
6	7.17	10	3.88
8	9.34	16	5.55
10	11.63	25	8.90
12	13.66	45	10.30

PART NUMBER	DESCRIPTION	PSI RATING
601883000000	3" X 10' GLOBAL ORANGE SPIRAL SUCTION HOSE	100
601859000000	4" X 10' GLOBAL ORANGE SPIRAL SUCTION HOSE	75
601863000000	6" X 10' GLOBAL ORANGE SPIRAL SUCTION HOSE	50
601867000000	8" X 10' GLOBAL ORANGE SPIRAL SUCTION HOSE	*
601871000000	12" X 10' GLOBAL ORANGE SPIRAL SUCTION HOSE	*
601857000000	3" X 20' GLOBAL ORANGE SPIRAL SUCTION HOSE	100
601861000000	4" X 20' GLOBAL ORANGE SPIRAL SUCTION HOSE	100
601865000000	6" X 20' GLOBAL ORANGE SPIRAL SUCTION HOSE	50
601869000000	8" X 20' GLOBAL ORANGE SPIRAL SUCTION HOSE	*
601873000000	12" X 20' GLOBAL ORANGE SPIRAL SUCTION HOSE	*
601904000000	3" X 10' CAM LOCK ORANGE SPIRAL SUCTION HOSE	100
601908000000	4" X 10' CAM LOCK ORANGE SPIRAL SUCTION HOSE	75
601912000000	6" X 10' CAM LOCK ORANGE SPIRAL SUCTION HOSE	50
601916000000	8" X 10' CAM LOCK ORANGE SPIRAL SUCTION HOSE	*
601906000000	3" X 20' CAM LOCK ORANGE SPIRAL SUCTION HOSE	100
601910000000	4" X 20' CAM LOCK ORANGE SPIRAL SUCTION HOSE	75
601914000000	6" X 20' CAM LOCK ORANGE SPIRAL SUCTION HOSE	50
601918000000	8" X 20' CAM LOCK ORANGE SPIRAL SUCTION HOSE	*